

## **AIRO S COMPRESSOR OIL**

PAO-BASED COMPRESSOR LUBRICANTS

## **Applications:**

The AIRO S PAO-based oil is fully synthetic compressor oil that is formulated with the highest quality polyalphaolefin (PAO) base fluids. These 100% premium synthetic oils are used where maximum seal, paint, and plastic compatibility is required.

These are designed for rotary screw applications and offer a service life of up to 8,000 hours under a wide range of temperatures under good operating conditions.

## **Typical Industrial Applications:**

- Rotary Screw Compressors
- Rotary Vane Compressors

Centrifugal CompressorsVacuum Pumps

## Performance Benefits:

- Outstanding thermal oxidative stability
- Very low pour point
- Wide operating temperature range
- Non-detergent and ashless
- Extended drain intervals / reduced oil disposal
- Excellent vapor pressure characteristics
- USDA H-2 authorized

TYPICAL PROPERTIES	TEST METHOD	Sigma
ISO Grade	ASTM D2422	46
Viscosity @ 40°C,cSt	ASTM D445	48
Viscosity @ 100°C,cSt	ASTM D445	7.9
Viscosity Index	ASTM D2270	134
Flash Point, °C/°F	ASTM D92	251/483
Pour Point, °C/°F	ASTM D97	-51/-60
Copper Corrosion	ASTM D130	1b, shiny
Foaming Sequences I, II, III	ASTM D892	Nil
Demulsibility	ASTM D1401	40-40-0(10)
Four Ball Wear, 40 Kg., 1200rpm, 75°C, 1 hr., Scar Diameter, mm	ASTM D4172	0.43
Specific Gravity	ASTM D1298	0.86